NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MS25487, REVISION G, NOTICE 1 AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MS25487, REVISION G, NOTICE 1. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS SAE TECHNICAL DOCUMENT.

CUSTODIAN: SAE AE-8/AE-8C1

PROCUREMENT SPECIFICATION: MIL-C-7974



AEROSPACE STANDARD

CONNECTOR, PLUG, ATTACHABLE EXTERNAL ELECTRIC POWER, AIRCRAFT, 28 VOLT DC, JET STARTING **AS25487** SHEET 1 OF 3

Copyright 2004 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

SSUED 2004-04

THIS MILITARY STANDARD IS APPROVED FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE. SELECTION FOR ALL NEW ENGINEERING AND DESIGN APPLICATIONS AND FOR REPETITIVE USE SHALL BE MADE FROM THIS DOCUMENT.




TABLE I

PART NO.	SUPERSEDES	WIRE SIZE	
		LARGE	SMALL
		SOCKETS	SOCKETS
MS25487-10	MS25487-1, -2, -9	0000	NO. 8




TABLE II

WIRE SIZE	E DIA		F DIA	
	MAXIMUM	MINIMUM	MAXIMUM	MINIMUM
0000	.780 (19.81 mm)	.760 (19.30 mm)	.645 (16.38 mm)	.622 (15.80 mm)
8	.272 (6.91 mm)	.260 (6.60 mm)	.186 (4.72 mm)	.176 (4.47 mm)



AEROSPACE STANDARD

NOTES:

- 1. MATERIAL: SEE PROCUREMENT SPECIFICATION.
- 2. MOLD OR STAMP WIRE SIZE ON CRIMP BARREL.
- 3. DIMENSIONS IN INCHES, UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ±.025 (±0.64 MM).
- 4. UNLESS OTHERWISE INDICATED, DIMENSIONS ARE SYMMETRICAL ABOUT CENTERLINES.
- 5. EACH PLUG WHEN MATED WITH MS25018-2 RECEPTACLE, SHALL MEET ALL THE REQUIREMENTS OF THE PROCUREMENT SPECIFICATION.
- 6. SOCKET CONTACT CRIMP TYPE BARREL ENDS SHALL BE DESIGNED SO THAT THE PLUG MAY BE ATTACHED TO CABLES USING CRIMPING TOOLS SPECIFIED IN MS20659.
- 7. ONLY NONCORROSIVE HARDWARE SHALL BE USED IN THE MANUFACTURE OF THE PLUG.
- 8. METRIC EQUIVALENTS (TO THE NEAREST .01 MM) ARE GIVEN FOR GENERAL INFORMATION ONLY AND ARE BASED ON 1 INCH = 25.4 MM.
- 9. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BIDS, OR REQUEST FOR PROPOSALS EXCEPT THAT REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.
- 10. FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

